

SAFETY DATA SHEET CONTACT TREATMENT OIL 2X

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME CONTACT TREATMENT OIL 2X
PRODUCT NO. ESOB200D
SUPPLIER ELECTROLUBE. A division of HK
WENTWORTH LTD
KINGSBURY PARK, MIDLAND
ROAD
SWADLINCOTE
DERBYSHIRE, DE11 0AN
UNITED KINGDOM
+44(0)1283 222 111
+44(0)1283 550 177

2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
Benzamine, N phenyl, reaction product with 2,4,4 trimethylpentene	270-128-1	68411-46-1	< 1%	N;R51/53.
DICHLOROMETHANE	200-838-9	75-09-2	10-30%	Carc3;R40

The Full Text for all R-Phrases are Displayed in Section 16

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels

3 HAZARDS IDENTIFICATION

Limited evidence of a carcinogenic effect.

CLASSIFICATION Carc 3;R40.

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol cans may explode in a fire.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers.

7 HANDLING AND STORAGE

CONTACT TREATMENT OIL 2X

USAGE PRECAUTIONS

Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Store at moderate temperatures in dry, well ventilated area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
DICHLOROMETHANE	WEL	100 ppm(Sk)	350 mg/m3(Sk)	300 ppm(Sk)	1060 mg/m3(Sk)

ENGINEERING MEASURES

No particular ventilation requirements.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. **DO NOT SMOKE IN WORK AREA!**

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol Liquid		
COLOUR	Colourless		
ODOUR	Characteristic		
VOLATILITY DESCRIPTION	Volatile.		
SOLUBILITY	Insoluble in water		
BOILING POINT (°C)	>200	MELTING POINT (°C)	N/D
RELATIVE DENSITY	1.000 @ 20 °c	BULK DENSITY	1000 kg/m3
VAPOUR PRESSURE	n/a kPa @ 19 °c	FLASH POINT (°C)	>210 CC (Closed cup).
AUTO IGNITION TEMPERATURE (°C)	>370		

10 STABILITY AND REACTIVITY

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with acids and alkalies.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire or high temperatures create: Carbon monoxide (CO). Hydrogen fluoride (HF). Carbonyl fluoride

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

Known or suspected carcinogen for humans.

INHALATION

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

Other Health Effects

Suspect Cancer Hazard. Carcinogen Category 3.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

The product is not expected to be hazardous to the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

CONTACT TREATMENT OIL 2X



UK ROAD CLASS	2		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	Not Applicable
ADR CLASS NO.	2	ADR CLASS	Class 2.2: Non-flammable, non-toxic gases.
ADR PACK GROUP	Not Applicable	ADR LABEL NO.	2 & 6.1
CEFIC TEC(R) NO.	20G5T	RID CLASS NO.	2
RID PACK GROUP	Not Applicable	UN NO. SEA	1950
IMDG CLASS	2	IMDG PAGE NO.	2.2 & 6.1
IMDG PACK GR.	Not Applicable	EMS	F-D, S-U
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1950	AIR CLASS	2.2
AIR SUB CLASS	6.1	AIR PACK GR.	Not Applicable

15 REGULATORY INFORMATION

LABELLING



Harmful

CONTAINS DICHLOROMETHANE

RISK PHRASES

R40 Limited evidence of a carcinogenic effect.

SAFETY PHRASES

- S23 Do not breathe vapour/spray.
- S36/37 Wear suitable protective clothing and gloves.
- S38 In case of insufficient ventilation, wear suitable respiratory equipment.
- A1 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
- A2 Do not spray on a naked flame or any incandescent material.
- S2 Keep out of the reach of children

UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC. Dangerous Substance Directive 67/548/EEC.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

GENERAL INFORMATION

CN No 38140090

CONTACT TREATMENT OIL 2X

REVISION COMMENTS

Revised in accordance with CHIP3 and EU Directives 1999/45/EC and 2001/58/EC

ISSUED BY

Helen O'Reilly

REVISION DATE NOVEMBER 2006

REV. NO./REPL. SDS GENERATED 3

SDS NO. 11470

RISK PHRASES IN FULL

R40 Limited evidence of a carcinogenic effect.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.